Section 1 PRODUCT AND COMPANY IDE	ENTIFICATION	
PRODUCT NUMBER	HMIS CODES Health	2*
CW01025		4 0
PRODUCT NAME		v
COLORWORKS* from KRYLON* Interior/Exterior		
MANUFACTURER'S NAME	EMERGENCY TELEPHONE NO.	
THE SHERWIN-WILLIAMS COMPANY	(216) 566-2917	
KRYLON Products Group		

KRYLON Products Group Cleveland, OH 44115

DATE OF PREPARATION 14-OCT-03

INFORMATION TELEPHONE NO. (800) 832-2541

% by WT	Section 2 CAS No.	COMPOSITION/INFORMATION ON INGREDIENTS INGREDIENT UNITS VAPOR PRESSURE
18	74-98-6	Propane ACGIH TLV 2500 ppm 760 mm
17	106-97-8	OSHA PEL 1000 ppm Butane ACGIH TLV 800 ppm 760 mm
3	64742-89-8	OSHA PEL 800 ppm Lt. Aliphatic Hydrocarbon Solvent
7	64742-89-8	ACĞIH TLV 100 ppm 53 mm OSHA PEL 100 ppm V. M. & P. Naphtha
		ACGIH TLV 300 ppm 12 mm OSHA PEL 300 ppm OSHA PEL 400 ppm STEL
12	108-88-3	Toluene ACGIH TLV 50 ppm (skin) 22 mm
1	95-63-6	OSHA PEL 100 ppm (skin) OSHA PEL 150 ppm (skin) STEL 1,2,4-Trimethylbenzene
	93-03-0	ACGIH TLV 25 ppm 2.03 mm OSHA PEL 25 ppm
2	111-76-2	2-Butoxyethanol ACGIH TLV 20 ppm (skin) 0.88 mm
24	67-64-1	OSHA PEL 20 ppm (skin) Acetone ACGIH TLV 500 ppm 180 mm
0 0	1222 07 4	ACGIH TLV 750 ppm STEL OSHA PEL 1000 ppm
0.8	1333-86-4	Carbon Black ACGIH TLV 3.5 mg/m3 OSHA PEL 3.5 mg/m3

CW01025 page 2

Section 3 -- HAZARDS IDENTIFICATION

ROUTES OF EXPOSURE

INHALATION of vapor or spray mist.

EYE or SKIN contact with the product, vapor or spray mist.

EFFECTS OF OVEREXPOSURE

EYES: Irritation.

SKIN: Prolonged or repeated exposure may cause irritation.

INHALATION: Irritation of the upper respiratory system.

May cause nervous system depression. Extreme overexposure may result in unconsciousness and possibly death. SIGNS AND SYMPTOMS OF OVEREXPOSURE

Headache, dizziness, nausea, and loss of coordination are indications of excessive exposure to vapors or spray mists.

Redness and itching or burning sensation may indicate eye or excessive skin exposure.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE

None generally recognized.

CANCER INFORMATION

For complete discussion of toxicology data refer to Section 11.

Section 4 -- FIRST AID MEASURES

Flush eyes with large amounts of water for 15 minutes. EYES:

Get medical attention.

SKIN: Wash affected area thoroughly with soap and water.

Remove contaminated clothing and launder before re-use.

INHALATION: If affected, remove from exposure. Restore breathing.

Keep warm and quiet.

INGESTION: Do not induce vomiting.

Get medical attention immediately.

Section 5 -- FIRE FIGHTING MEASURES

LEL UEL 0.9 12.8 FLASH POINT

Propellant < 0 FEXTINGUISHING MEDIA

Carbon Dioxide, Dry Chemical, Foam UNUSUAL FIRE AND EXPLOSION HAZARDS

Containers may explode when exposed to extreme heat.

Application to hot surfaces requires special precautions.

During emergency conditions overexposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent. Obtain medical attention.

SPECIAL FIRE FIGHTING PROCEDURES

Full protective equipment including self-contained breathing apparatus should be used.

Water spray may be ineffective. If water is used, fog nozzles are preferable. Water may be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat.

CW01025 page 3

Section 6 -- ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED Remove all sources of ignition. Ventilate the area. Remove with inert absorbent.

Section 7 -- HANDLING AND STORAGE

STORAGE CATEGORY

Not Available

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE

Keep away from heat, sparks, and open flame. Vapors will accumulate

readily and may ignite explosively.

During use and until all vapors are gone: Keep area ventilated - Do not smoke - Extinguish all flames, pilot lights, and heaters - Turn off stoves, electric tools and appliances, and any other sources of ignition.

Consult NFPA Code. Use approved Bonding and Grounding procedures. Contents under pressure. Do not puncture, incinerate, or expose to temperature above 120F. Heat from sunlight, radiators, stoves, hot water, and other heat sources could cause container to burst. Do not take internally. Keep out of the reach of children.

Section 8 -- EXPOSURE CONTROLS/PERSONAL PROTECTION

PRECAUTIONS TO BE TAKEN IN USE

Use only with adequate ventilation.

Avoid contact with skin and eyes. Avoid breathing vapor and spray mist.

Wash hands after using.

This coating may contain materials classified as nuisance particulates (listed "as Dust" in Section 2) which may be present at hazardous levels only during sanding or abrading of the dried film. If no specific dusts are listed in Section 2, the applicable limits for nuisance dusts are ACGIH TLV 10 mg/m3 (total dust), 3 mg/m3 (respirable fraction), OSHA PEL 15 mg/m3 (total dust), 5 mg/m3 (respirable fraction).

Removal of old paint by sanding, scraping or other means may generate dust or fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse health effects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup. For more information, call the National Lead Information Center at 1-800-424-LEAD (in US) or contact your local health authority.

Local exhaust preferable. General exhaust acceptable if the exposure to materials in Section 2 is maintained below applicable exposure limits. Refer to OSHA Standards 1910.94, 1910.107, 1910.108. RESPIRATORY PROTECTION

If personal exposure cannot be controlled below applicable limits by ventilation, wear a properly fitted organic vapor/particulate respirator approved by NIOSH/MSHA for protection against materials in Section 2.

When sanding or abrading the dried film, wear a dust/mist respirator approved by NIOSH/MSHA for dust which may be generated from this product, underlying paint, or the abrasive.

CW01025 page 4

PROTECTIVE GLOVES

None required for normal application of aerosol products where minimal skin contact is expected. For long or repeated contact, wear chemical resistant gloves.

EYE PROTECTION

Wear safety spectacles with unperforated sideshields.

OTHER PRECAUTIONS

Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. _______

Section 9 -- PHYSICAL AND CHEMICAL PROPERTIES

5.84 lb/gal 700 g/l PRODUCT WEIGHT SPECIFIC GRAVITY 0.70 <0 - 343 F <-18 - 172 CBOILING POINT MELTING POINT Not Available VOLATILE VOLUME 92 Faster than ether EVAPORATION RATE VAPOR DENSITY Heavier than air SOLUBILITY IN WATER N.A. 7.0

VOLATILE ORGANIC COMPOUNDS (VOC Theoretical)

Volatile Weight 63.23 % Less Water and Federally Exempt Solvents

Section 10 -- STABILITY AND REACTIVITY

STABILITY -- Stable CONDITIONS TO AVOID

None known. INCOMPATIBILITY

None known.

HAZARDOUS DECOMPOSITION PRODUCTS

By fire: Carbon Dioxide, Carbon Monoxide

HAZARDOUS POLYMERIZATION

Will not occur

Section 11 -- TOXICOLOGICAL INFORMATION

CHRONIC HEALTH HAZARDS

Carbon Black is classified by IARC as possibly carcinogenic to humans (group 2B) based on experimental animal data, however, there is insufficient evidence in humans for its carcinogenicity.

Prolonged overexposure to solvent ingredients in Section 2 may cause adverse effects to the liver, urinary, blood forming, cardiovascular and reproductive systems.

Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage.

TOXICOLOGY DATA

CW01025	pa	ae	5

CAS No.							
LC50 RAT	CAS No.	Ingredient Na	====== ame				
LC50 RAT	74-98-6	Propane					
LC50	, , , , , ,	1 10 10 1110	LC50	RAT	4HR	Not Available	
LC50 RAT AHR Not Available LD50 RAT AHR Not Available Not			LD50	RAT		Not Available	
LD50 RAT	106-97-8	Butane	T 0 F 0	D.71 ED	4110		
Lt. Aliphatic Hydrocarbon Solvent LC50 RAT 4HR Not Available LD50 RAT Not Available Not Available LC50 RAT 4HR 4000 ppm LD50 RAT 5000 mg/kg P5-63-6 LC50 RAT 4HR Not Available					4HR		
LC50 RAT AHR Not Available LD50 RAT AHR Not Available Not Available Not Available Not Available LC50 RAT AHR Not Available LD50 RAT AHR Not Available LD50 RAT AHR Not Available LD50 RAT AHR AU00 ppm LD50 RAT S000 mg/kg 1.2,4-Trimethylbenzene LC50 RAT AHR Not Available LD50 RAT ARA ACetone LC50 RAT AHR Not Available LD50 RAT AHR Not Available LD50 RAT ARA ACETONE LC50 RAT AHR Not Available LD50 RAT AHR Not Available LC50 RAT AHR Not Available	64742-89-8	It Δliphatic			Solvent	NOU AVAILABLE	
LD50 RAT	04/42 05 0	ne. Arrphacre	LC50	RAT	4HR	Not Available	
LC50 RAT					1111		
LD50 RAT	64742-89-8	V. M. & P. Na					
108-88-3 Toluene LC50 RAT 4HR 4000 ppm LD50 RAT 5000 mg/kg 95-63-6 1,2,4-Trimethylbenzene LC50 RAT 4HR Not Available LD50 RAT Not Available LD50 RAT 4HR Not Available LC50 RAT 4HR Not Available LC50 RAT 4HR Not Available LD50 RAT 470 mg/kg 67-64-1 Acetone LC50 RAT 4HR Not Available LD50 RAT 5800 mg/kg 1333-86-4 Carbon Black LC50 RAT 4HR Not Available					4HR		
LC50 RAT	100 00 2	T-1	LD50	RA'I'		Not Available	
LD50 RAT 5000 mg/kg 95-63-6 1,2,4-Trimethylbenzene LC50 RAT 4HR Not Available LD50 RAT Not Available LD50 RAT 4HR Not Available LD50 RAT 470 mg/kg 470 mg/kg LC50 RAT 4HR Not Available LD50 RAT 4HR Not Available LD50 RAT 5800 mg/kg 1333-86-4 Carbon Black LC50 RAT 4HR Not Available LC50 RAT 4	108-88-3	loluene	T C 5 O	D 7\ T'	ЛПБ	4000 rorm	
95-63-6					4111		
$\begin{array}{c ccccccccccccccccccccccccccccccccccc$	95-63-6	1.2.4-Trimeth				ooo o mg/ ng	
111-76-2 2-Butoxyethanol		, ,	ĪC50		4HR	Not Available	
$ \begin{array}{cccccccccccccccccccccccccccccccccccc$				RAT		Not Available	
$ \begin{array}{cccccccccccccccccccccccccccccccccccc$	111-76-2	2-Butoxyethar			ALLD	NT - +	
67-64-1 Acetone LC50 RAT 4HR Not Available LD50 RAT 5800 mg/kg 1333-86-4 Carbon Black LC50 RAT 4HR Not Available					4HK		
LC50 RAT 4HR Not Available LD50 RAT 5800 mg/kg 1333-86-4 Carbon Black LC50 RAT 4HR Not Available	67-64-1	Acetone	ПРЭО	NAI		470 mg/kg	
LD50 RAT 5800 mg/kg 1333-86-4 Carbon Black LC50 RAT 4HR Not Available	0, 01 1	110000110	LC50	RAT	4HR	Not Available	
LC50 RAT 4HR Not Available			LD50				
	1333-86-4	Carbon Black			_		
					4HR		
LD50 RAT Not Available			 _TD20	KA1		NOL AVAILADIE	

Section 12 -- ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL INFORMATION

No data available.

Section 13 -- DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD

Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261.

Waste must be tested for ignitability to determine the applicable EPA

hazardous waste numbers.

Do not incinerate. Depressurize container. Dispose of in accordance with Federal, State/Provincial, and Local regulations regarding pollution.

Section 14 -- TRANSPORT INFORMATION

No data available.

CW01025 page 6

Section 15 -- REGULATORY INFORMATION

SARA 313 (40 CFR 372.65C) SUPPLIER NOTIFICATION

CAS No.	CHEMICAL/COMPOUND	% by WT	% Element
108-88-3 95-63-6	Toluene 1,2,4-Trimethylbenzene Glvcol Ethers	12 1 1 2	

CALIFORNIA PROPOSITION 65

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. TSCA CERTIFICATION

All chemicals in this product are listed, or are exempt from listing, on the TSCA Inventory.

Section 16 -- OTHER INFORMATION

This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.

The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.