ONE L	UBE AEROSOL		
1. PRODUCT AND COMPANY IDENTIF Product Name: ONE LUBE AEROSOL Product Use: Lubricant Synonyms: 43712012	TCATION		mber: 1548. Date: 6/19/200
Manufacturer Blue Coral/Slick 50 Ltd. 5700 South Lee Road Maple Heights, OH 44137 USA	Phone Numbers Medical Emergency: Transportation Eme Transportation Eme 1-352- MSDS Assistance: 1- Fax On Demand: 1-8 Technical Assistance Customer Service: 1- Fax Number: 713-21 Internet Address: w	rgency (USA): 1-8 rgency (International Section 2323-3500) (Call Control Section 2323-3500) (Call C	onal): llect)
2. COMPONENT INFORMATION			
Component	CAS No.	Weight Percent Range	Hazardous in Blend
HEAVY PARAFFINIC SOLVENT DEWAXED DISTILLATES	0 64742-65-0	< 70	No
HEPTANE	142-82-5	< 30	Yes
CARBON DIOXIDE	124-38-9	1 - 5	Yes
This product is HAZARDOUS according to OSF Hazards: Flammable/Combustible X Acute Toxin Pressure X Reactive Exposure Lin Other: No information available		Carcinogen Other	_
3.HAZARDS IDENTIFICATION			
Emergency and Hazards Overview DANGER: FLAMMABLE (OR EXTREMELY SWALLOWED, VAPOR HARMFUL, CONTE			F
NFPA Ratings: Health 1 Flammabili	ity 3 Reactivity	0	
Primary Route of Exposure: Skin X Inl	nalation X Eye		

Health Effect Information

Eye Contact: Avoid eye contact. This product may be slightly irritating to the eyes upon direct contact Based on testing of similar products and or components. Exposure to high concentrations of vapors may be irritating to the eyes.

Skin Contact: Avoid skin contact. This product may cause slight skin irritation upon direct contact.

Based on testing of similar products and or components. Prolonged or repeated skin contact may result in dryness, chapping, and reddening. May be absorbed through skin. See Section 11 - Toxicological Information.

ONE LUBE AEROSOL

Inhalation: Avoid prolonged inhalation of vapors. Acute and chronic exposure to vapors may be irritating to the respiratory tract. Severe intoxication may lead to drowsiness, dullness, numbness, and headache followed by dizziness, weakness, and nausea. Intentional misuse by deliberately concentrating and inhaling this product can be harmful or fatal.

Aspiration may lead to chemical pneumonitis which is characterized by pulmonary edema and nemorrhage and may be fatal. Signs of lung involvement include increased respiratory rate, increased heart rate, and a bluish discoloration of the skin. Coughing, choking, and gagging are often noted at the time of aspiration. Gastrointestinal discomfort may develop, followed by vemiting with a further risk of aspiration. Severe oral intoxication will lead to intense burning of the threat and may result in drowsiness, dullness, numbness, and headache followed by dizziness, weakness, and nausea. Loss of consciousness and convulsions followed by death may result.

Medical Conditions Aggravated by Exposure: Drying and chapping may make the skin more susceptible to other irritants, sensitizers and disease.

Other: No information available

MSDS Number: 15483

4. FIRST AID INFORMATION

Eye Contact: Immediately flush eyes with large amounts of water and continue flushing until irritation subsides. If irritation persists, seek medical attention.

Skin Contact: No treatment is necessary under ordinary circumstances. Remove contaminated clothing. Wash contaminated area thoroughly with soap and water. If redness or irritation occurs and persists, seek medical attention. Use a hand or skin lotion to prevent dryness.

Inhalation: If victim exhibits signs of vapor intoxication remove to fresh air. If discomfort persists seek medical attention.

Ingestion: Do not induce vomiting due to aspiration hazard. If vomiting occurs lower head below knees to avoid aspiration. Seek immediate medical attention.

Notes to Physician: No information available

Other: No information available

5. FIRE AND EXPLOSION INFORMATION

Flammable Properties

Flash Point (aerosol concentrate) 18 F. -7 8 C

Flame Extension: > 18", no flashback

Flammable Limits in Air

Upper Percent: No data available Lower Percent: No data available

Autoignition Temperature: No data available

Test Method: ASTM D-56 (T.C.C.)

Test Method: CPSC 1500 45

Test Method: No information available

NFPA Classification: Level 3 Aerosol (NFPA 30B)

Extinguishing Media: Use water spray (fog), dry chemical, foam, or carbon diexide

Fire Fighting Measures

Special Fire Fighting Procedures and Equipment: No special fire fighting procedures are required.

Unusual Fire and Explosion Conditions: Dense smoke may be generated while burning. Carbon monoxide, carbon dioxide, and other oxides may be generated as products of combustion.

Page 2 of 8

ONE LUBE AEROSOL

Page 3 of 8 MSDS Number: 15483

Hazardous Combustion By-Products: None

Other: No information available

ACCIDENTAL RELEASE MEASURES

Personnel Safeguards: Remove all sources of ignition. Provide adequate ventilation during clean-up. Consult Health Effect Information in Section 3, Personal Protection Information in Section 8, Fire and Explosion Information in Section 5, and Stability and Reactivity Information in Section 10.

Regulatory Notifications: No notification required

Containment and Clean up: Do not allow spill to enter sewers or watercourses. Absorb with solvent absorbent material

Other: No information available

7. HANDLING AND STORAGE INFORMATION

Handling: Do not open or use in unventilated, enclosed or confined spaces. All ignition sources in the area should be controlled. Fire extinguishers should be kept readily available. See NFPA 30 and OSHA 1910.106--Flammable and Combustible Liquids

Storage: Do not transfer to unmarked containers. Store in a cool, well ventilated area in closed containers away from heat, sparks, open flame or oxidizing materials

Empty Container Warnings

Drums: Not applicable

Plastic: Empty container may retain product residues. Do not reuse this container

Other: No information available

8. EXPOSURE CONTROLS / PERSONAL PROTECTION INFORMATION

Exposure Limits and Guidelines

Component	CAS No.	Exposure Limit
HEPTANE	142-82-5	OSHA - PEL: TWA 500 ppm
		ACGIH - TLV: TWA 400 ppm
		ACGIH - TLV: STEL 500 ppm
CARBON DIOXIDE 124-38-9	OSHA - PEL: TWA 5000 ppm	
		ACGIH - TLV: TWA 5000 ppm
	ACGIH - TLV. STEL 30000 ppm	

Personal Protective Equipment

Eye/Face Protection: Eye protection is not required under conditions of normal use. If material is handled such that it could be splashed into eyes, wear plastic face shield or splash-proof safety goggles.

Skin Protection: No skin protection is required for single, short duration exposures. For prolonged or repeated exposures, use impervious clothing (boots, gloves, aprons, etc.) over parts of the body subject to exposure. Launder soiled clothes

ONE LUBE AEROSOL

Respiratory Protection: Respiratory protection is not required under conditions of normal use. If excessive levels of mists or vapors are generated while using this product, use an organic vapor respirator. All respirators must be NIOSH certified. See Section 3, Health Effect Information,

Inhalation

MSDS Number: 15483

Personal Hygiene: Consumption of food and beverage should be avoided in work areas where hydrocarbons are present. Always wash hands and face with soap and water before eating, drinking, or smoking.

Engineering Controls / Work Practices

Ventilation: General room ventilation is normally sufficient to prevent buildup of hazardous concentrations. If product is used in enclosed or confined spaces, adequate ventilation must be provided to prevent buildup of vapors or mists. See also Fire and Explosion Information in Section.

Other: The OSHA PEL for petroleum distillates is 2000 mg/m3. NIOSH recommended limits for petroleum distillates are 350 mg/m3 (10-hr TWA) and 1800 mg/m3 (15-min ceiling).

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Clear		
Odor: Solvent	Vapor Pressure: No data available	
Physical state: Aerosol	Vapor Density (air=1): No data available	
pH: No data available	Percent Volatile by Volume: No data available	
Boiling Point: No data available	Volatile Organic Content: No data available	
Melting Point: No data available	Molecular Weight: No data available	
Specific Gravity: 0.83	Average Carbon Number: No data available	
Pour Point: No data available	Viscosity @ 100 F: No data available	
	Viscosity @ 40 C: No data available	
Solubility in Water: Nil in water		
Octanol / Water Coefficient: Log Kow = N	o data available	

10. STABILITY AND REACTIVITY INFORMATION

Chemical Stability: Stable

Conditions to Avoid: High heat and open flames.

Incompatible Materials to Avoid: May react with strong exidizing agents

Other: No information available

11. TOXICOLOGICAL INFORMATION

Primary Eye Irritation: No information available

Primary Skin Irritation: No information available

Acute Dermal Toxicity: No information available

Subacute Dermal Toxicity: No information available

Dermal Sensitization: No information available

Inhalation Toxicity: No information available

Page 4 of 8

ONE LUBE AEROSOL

MSDS Number: 15483 Page 5 of 8

Inhalation Sensitization: No information available

Oral Toxicity: No information available

Mutagenicity: No information available

Carcinogenicity: Light hydrocarbons such as stoddard solvent, VM & P naphtha and C10-C11 isoparaffins have produced kidney damage in male rats, but not in female rats or mice. The Environmental Protection Agency (EPA) has concluded that rat kidney damage and tumors induced by light petroleum hydrocarbons are not relevant to humans. Various naphthas tested were not carcinogenic in mouse skin painting studies conducted by the American Petroleum Institute (API). The International Agency for Research on Cancer (IARC) has concluded that petroleum solvents are Group 3 substances, "not classifiable as to their carcinogenicity to humans"

Reproductive and Developmental Toxicity: No information available

Teratogenicity: No information available

Immunotoxicity: No information available

Neurotoxicity: No information available

Other: No information available

12. ECOLOGICAL INFORMATION

Aquatic Toxicity: May be toxic to aquatic organisms.

Terrestrial Toxicity: No information available

Chemical Fate and Transport: No information available

Other: No information available

13. DISPOSAL INFORMATION

Regulatory Information: Dispose of residual products and empty containers responsibly Refer to state and local regulations for additional disposal requirements.

Waste Disposal Methods: Waste material may be landfilled or incinerated at an approved facility

Other: No information available

14. TRANSPORTATION INFORMATION

U.S. Department of Transportation (DOT)

Highway / Rail (Bulk): Not Regulated Highway / Rail (Non-Bulk): Regulated

The DOT description is provided to assist in the proper shipping classification of this product and may not be suitable for all shipping descriptions.

MSDS Number: 15483

ONE LUBE AEROSOL

Page 6 of 8

International Information Vessel: IMDG Regulated: X IMDG Not Regulated:					
Air: ICAO Regulated: X ICAO Not Regulated:					
Other: No information available					
15. Regulatory Information					
Regulatory Lists Searched: The components listed in Section 2 of this MSDS were compared to substances that appear on the following regulatory lists. Each list is numerically identified. See Regulatory Search Results below.					
Health & Safety: 10 - IARC carcinogen, 11 - NTP carcinogen, 12 - OSHA carcinogen, 15 - ACGIH TLV. 16 - OSHA PEL, 17 - NIOSH exposure limit. 20 - US DOT Appendix A, Hazardous substances, 22 - FDA 21 CFR Total food additives, 23 - NFPA 49 or 325					
Environmental: 30 - CAA 1990 Hazardous air pollutants, 31 - CAA Ozone depletors, 33 - CAA HON rule, 34 - CAA Toxic substance for accidental release prevention, 35 - CAA Volatile organic compounds (VOC's) in SOCMI, 41 - CERCLA / SARA Section 302 extremely hazardous substances, 42 - CERCLA / SARA Section 313 emissions reporting, 43 - CWA Hazardous substances, 44 - CWA Priority pollutants, 45 - CWA Toxic pollutants, 46 - EPA Proposed test rule for hazardous air pollutants, 47 - RCRA Basis for listing - Appendix VII, 48 - RCRA waste, 49 - SDWA - (S)MCLs					
International: 50 - Canada - WHMIS Classification of substance, 54 - Mexico - Drinking water - ecological criteria, 55 - Mexico - Wastewater discharges, 56 - US -TSCA Section (12)(b) - export notification					
State Lists: 60 - CA - Proposition 65, 61 - FL - Substances, 62 - MI - Critical materials, 63 - MA - RTK, 61 - MA - Extraordinarily hazardous substances, 65 - MN - Hazardous substances, 66 - PA - RTK, 67 - NJ - RTK, 68 - NJ - Environmental hazardous substances, 69 - NJ - Special hazardous substances					
Inventories: 80 - Canada - Domestic substances, 81 - European - EINECS, 82 - Japan - ENCS, 83 - Korea - Existing and evaluated chemical substances, 84 - US - TSCA , 85 - China Inventory					
RegulatorySearch Results: CARBON DIOXIDE: 15, 16, 17, 22, 50, 61, 63, 65, 66, 67, 69, 80, 81, 82, 83, 84, 85 HEAVY PARAFFINIC SOLVENT DEWAXED DISTILLATES: 80, 81, 83, 84, 85 HEPTANE: 15, 16, 17, 23, 50, 61, 63, 65, 66, 67, 69, 80, 81, 82, 83, 84, 85					
U.S. TSCA Inventory; All components of this material are on the U.S. TSCA Inventory.					
SARA Section 313: Consumer products are not regulated under SARA, Title III, Section 313.					
IARC: No information available					
SARA 311/312 Categories Acute: X Chronic: Fire: X Pressure: Reactive: Not Regulated:					
Canadian WHMIS Classification Class A - Compressed gas Class B - Flammable and Combustible Material, Division 5, Flammable Aerosols Class D - Poisonous and infectious material, Division 2B, Toxic Material					

MSDS Number: 15483

ONE LUBE AEROSOL

Page 7 of 8

European Union Classification

Hazard Symbols:

No information available

Risk Phrases:

No information available

Safety Phrases:

No information available

Other: No information available

16. OTHER INFORMATION

Health and Environmental Label Language

Front Label:

DANGER: FLAMMABLE (OR EXTREMELY FLAMMABLE). HARMFUL OR FATAL IF SWALLOWED. VAPOR HARMFUL. CONTENTS UNDER PRESSURE. Read carefully other cautions on back.

Back Label:

DANGER: Contains hydrocarbon solvents. Prolonged and repeated skin contact may cause drying of skin.

PRECAUTIONARY MEASURES. Do not puncture, incinerate or store above 120 F. Avoid prolonged exposure to sunlight. Keep away from heat, sparks, flames and other ignition sources. Exposure to heat may cause can to burst. Avoid breathing of mists and vapors. Use only in well ventilated areas. Avoid skin and eye contact. Wash thoroughly after handling.

FIRST AID: If swallowed, do not induce vomiting. Call physician immediately. For eye contact, wash thoroughly with water. If inhaled, breathe fresh air. If not breathing, give artificial respiration. Call physician immediately. Use only as directed. Intentional misuse by deliberately concentrating and/or inhaling can be harmful or fatal.

KEEP OUT OF REACH OF CHILDREN

Note: For automotive products used near engine, add on top of back panel. Keep away from battery terminals.

MSDS Revisions

Previous Version Date: 6 30 1998

Previous Version Information

Revised all sections, new 16 section MSDS format

Other

No information available

Prepared By:

Pennzoil-Quaker State Company Environmental, Safety, Health, & DOT Compliance P. C. Box 2967 Houston, TX 77252-2967 USA

MSDS Number: 15483

ONE LUBE AEROSOL

Disclaimer of Warranty: The information contained herein is based upon data and information available to us, and reflects our best professional judgement. This product may be formulated in part with components purchased from other companies. In many instances, especially when proprietary or trade secret materials are used, Pennzoil-Quaker State Company must rely upon the hazard evaluation of such components submitted by that product's manufacturer or importer. No warranty of merchantability, fitness for any use, or any other warranty is expressed or implied regarding the accuracy of such data or information. The results to be obtained from the use thereof, or that any such use does not infringe any patent. Since the information contained herein may be applied under conditions of use beyond our control and with which we may be unfamiliar, we do not assume responsibility for the results of such application. This information is furnished upon the condition that the person receiving it shall make his own determination of the suitability of the material for his particular use

Page 8 of 8