Material Safety Data Sheet



QUIK FILL 320

Section 1. Chemical product and company identification

Product use

: QUIK FILL 320 Floor Stripper

Supplier

Ecolab Inc. Professional Products Division

370 N. Wabasha St. St. Paul, MN 55102 1-800-247-5362

Code

: 903580

Date of issue

: 13-January-2006

EMERGENCY HEALTH INFORMATION: 1-800-328-0026 Outside United States and Canada CALL 1-651-222-5352 (in USA)

Section 2. Composition, information on ingredients

Name	CAS number	% by weight
2-butoxyethanol	111-76-2	25
sodium hydroxide	1310-73-2	5
2-aminoethanol	141-43-5	5 - 20
xylenesulfonic acid, sodium salt	1300-72-7	1-5
alcohols, c12-16, ethoxylated	68551-12-2	1 - 5

Section 3. Hazards identification

Physical state

: Liquid. (Liquid.)

Emergency

: DANGER!

overview

CAUSES EYE AND SKIN BURNS.

CAUSES SEVERE RESPIRATORY TRACT IRRITATION.

HARMFUL IF SWALLOWED.

Do not ingest. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Keep container closed. Use only with adequate ventilation. Wash thoroughly after handling.

The state of the state of a

Potential acute health effects

Eyes

: Corrosive to eyes. : Corrosive to the skin.

Skin

: Severely irritating to the respiratory system.

Inhalation

: Harmful if swallowed. Causes burns to mouth, throat and stomach.

Ingestion See toxicological information (section 11)

Section 4. First aid measures

Eye contact

In case of contact, immediately flush eyes with cool running water. Remove contact lenses and continue flushing with plenty of water for at least 15 minutes. Get medical attention

immediately.

Skin contact

: In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. Clean shoes

thoroughly before reuse. Get medical attention immediately.

Inhalation

: If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult,

give oxygen. Get medical attention immediately.

Ingestion

Get medical attention immediately. Do not induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth; then drink one or two large glasses of water. Get

medical attention immediately.

QUIK FILL 320

Page: 2/4

Section 5. Fire fighting measures

Flash point

Fire-fighting media and instructions

Use an extinguishing agent suitable for the surrounding fire.

Dike liquid for later disposal.

No specific hazard.

for fire-fighters

Special protective equipment: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure

Section 6. Accidental release measures

Personal precautions : Ventilate area of leak or spill. Do not touch damaged containers or spilled material unless wearing appropriate protective equipment (Section 8). Stop leak if without risk. Do not allow to enter drains or watercourses.

Environmental precautions

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and

Methods for cleaning up

: If emergency personnel are unavailable, contain spilled material. For small spills, add absorbent (soil may be used in the absence of other suitable materials), scoop up material and place in a sealable, liquid-proof container for disposal. For large spills, dike spilled material or otherwise contain material to ensure runoff does not reach a waterway. Place spilled material in an appropriate container for disposal.

Section 7. Handling and storage

Handling

: Do not ingest. Do not get in eyes, on skin or on clothing. Keep container closed. Use only with

adequate ventilation. Do not breathe vapor or mist. Wash thoroughly after handling.

Storage

Keep container tightly closed. Keep container in a cool, well-ventilated area.

Store between 15 and 45°C

Section 8. Exposure controls, personal protection

Engineering controls

: Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective occupational exposure limits. Provide eyewash and safety shower in area if contact or splash hazard exists.

Personal protection

Eyes

Use chemical splash goggles. For continued or severe exposure wear a face shield over the

Hands

Respiratory

: Wear any impervious glove.

Skin

: Wear synthetic apron, other protective equipment as necessary to prevent skin contact. : Wear appropriate respirator when ventilation is inadequate and occupational exposure limits

are exceeded.

Name

Exposure limits

2-butoxyethanol

ACGIH TLV (United States, 1/2004). TWA: 20 ppm 8 hour/hours. Form: All forms OSHA PEL (United States, 8/1997). Skin TWA: 240 mg/m³ 8 hour/hours. Form: All forms TWA: 50 ppm 8 hour/hours. Form: All forms

2-aminoethanol

ACGIH TLV (United States, 1/2004).

STEL: 15 mg/m³ 15 minute/minutes. Form: All forms STEL: 6 ppm 15 minute/minutes. Form: All forms TWA: 7.5 mg/m3 8 hour/hours. Form: All forms TWA: 3 ppm 8 hour/hours. Form: All forms OSHA PEL (United States, 8/1997).

TWA: 6 mg/m3 8 hour/hours. Form: All forms TWA: 3 ppm 8 hour/hours. Form: All forms

sodium hydroxide

OSHA PEL (United States, 8/1997).

TWA: 2 mg/m3 8 hour/hours. Form: All forms

ACGIH TLV (United States, 1/2004).

CEIL: 2 mg/m3

QUIK FILL 320 Page: 3/4

Section 9. Physical and chemical properties

Physical state

: Liquid. (Liquid.)

Color

: Red.

Odor pH : Pungent. : 13.25 (100%)

Boiling/condensation

: 100 °C

point

Specific gravity

: 1.05 (Water = 1)

Section 10. Stability and reactivity

Stability

: The product is stable.

Reactivity

: Highly reactive with acids.

Reactive with metals.

Section 11. Toxicological information

Potential acute health effects

Eyes

: Corrosive to eyes.

Skin

: Corrosive to the skin.

Inhalation

: Severely irritating to the respiratory system.

Ingestion

: Harmful if swallowed. Causes burns to mouth, throat and stomach.

Chronic effects on

humans

: Contains material which causes damage to the following organs: blood, kidneys, lungs, liver, lymphatic system, upper respiratory tract, skin, central nervous system (CNS), eye,

lens or cornea.

Section 12. Ecological information

Products of degradation

: These products are carbon oxides (CO, CO₂) and water, nitrogen oxides (NO, NO₂ etc.), sulfur oxides (SO₂, SO₃ etc.). Some metallic oxides.

Section 13. Disposal considerations

Waste disposal

: The generation of waste should be avoided or minimized wherever possible. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Waste

: Unused product is D002 (Corrosive)

classification

Consult your local or regional authorities.

Section 14. Transport information							
Regulatory information	UN number	Proper shipping name	Class	Packing group	Additional information		
DOT Classification	UN1719	Caustic alkali liquids, n.o.s. (sodium hydroxide, 2-aminoethanol)	8	li l	Limited quantity Yes. Special provisions B2, IB2, T11, TP2, TP27		

APPLIES ONLY DURING ROAD TRANSPORT

Any variation of the shipping description based on the packaging is not addressed.

QUIK FILL 320 Page: 4/4

Section 15. Regulatory information

HCS Classification

Corrosive material Target organ effects

U.S. Federal regulations

SARA 302/304/311/312 extremely hazardous substances: No products were

SARA 302/304 emergency planning and notification: No products were found.

TSCA 8(b) inventory

: All materials are listed or exempt.

Concentration

SARA 313 Form R - Reporting requirements : 2-butoxyethanol

Product name

24.75

California Prop. 65

: No products were found.

Section 16. Other information

Hazardous Material

Information System (U.S.A.)

0 Fire hazard 0 Reactivity С Personal protection

Date of issue

: 13-January-2006.

Responsible name

: Regulatory Affairs

Date of previous issue

: No previous validation.

Notice to reader

The above information is believed to be correct with respect to the formula used to manufacture the product in the country of origin. As data, standards, and regulations change, and conditions of use and handling are beyond our control, NO WARRANTY, EXPRESS OR IMPLIED, IS MADE AS TO THE COMPLETENESS OR CONTINUING ACCURACY OF THIS INFORMATION.