

City of Choctaw Occupancy & Zoning Application

☐ New Business

☐ Change of Original Applicant

	☐ Change of Te	nant 🗆	Change	of Owner	ship		
Occupancy Permit No.:		\$60.00	Receip	t No.: RN-	Pay	ment Type:	
Zoning Permit No.:							
Business Name:							
Business Mailing Address: _							
Business Physical Address: _							
Owner/Corp. Name:							
E-mail:							
Owner/Corp. Phone No.: (_							
Fax No.: ()		Em	ergency	/ No.: ()		
Owner/Corp. Mailing Addre	ss:						
If Corporation, list officers:							
Owner of Property:				Signed	d Copy of Leas	e □ Yes □ No	
Type of Use:		Curr	ent Zon	ing:	Require	ed Zoning:	
Building Size:	Total Square Ft	t:					
State Sales Tax #: STS		MMJ			Fed ID #:		
Able Permit 🛛 Required	☐ Not Require	d Re	newal D	ate/_	/		
OMMA License #'s: <u>D/</u>		P/			G/		
Check ALL that apply:	□ Dispensary	☐ Proces	sor 🗆	Grow □	Transportatio	n	
OBN License #'s: <u>D/</u>		P/			G/		
Department of Human Serv	ices &/or Health I	nspection				☐ Yes ☐ No	□NR
Department of Environmen	tal Quality Permit	:				☐ Yes ☐ No	□NR
	****DO NO	OT WRITE	BELOW	THIS LINE	****		
Current Zoning:			Cha	ange of zoi	ning required	☐ Yes ☐ No)
Zoning/Development Cento	er: [☐ Approv	ved □	Denied I	Ву:		_
Building Inspection:	Ι	☐ Approv	/ed □	Denied I	Ву:		_
Re-Inspection Required:	1	□ No □	Yes if	yes, when	n:		
Inspector					Date		 -
							
Owner/Manager					Date		

Existing Site

**	No	Change to construction of building and/or use. (Non-Conforming	3)	
		Is proper lot condition and maintenance being performed	[] Yes []	No [] N/A
		to the existing parking lot, driveways, and/or loading and		
		unloading zones? With special attention to holes.		
		Is proper line stripping for parking spaces, loading and unloading	[] Yes []	No [] N/A
		areas and fire lanes legible?		
		Is the loading and unloading area designated?	[] Yes []	No [] N/A
		Is outdoor lighting arranged to not interfere with adjacent use	[] Yes []	No [] N/A
		and/or adjacent street? (No flashing or intermittent type.)		
		No obstacles interfering within the line of sight triangle.	[] Yes []	No [] N/A
		Proper screening in place adjacent to a residential district	[] Yes []	No [] N/A
		Is trash bin screening in place?	[] Yes []	No [] N/A
		Improvement to Site		
*	An	addition, change of use. (Conformance)		
		Adequate amount of parking spaces	[] Yes []	No [] N/A
		All parking spaces, driveways, loading and unloading for	[] Yes []	No [] N/A
		shipment and ADA parking shall be paved with a sealed		
		surface pavement.		
		Designated loading and unloading zones	[] Yes []	No [] N/A
		No obstacles interfering within the line of sight triangle.	[] Yes []	No [] N/A
		Are all structures located in the proper setback laws?	[] Yes []	No [] N/A
		Is outdoor lighting arranged to not interfere with adjacent use	[] Yes []	No [] N/A
		and/or adjacent street? (No flashing or intermittent type.)		
		Proper screening in place adjacent to a residential district		No [] N/A
		Is trash bin screening in place?		No [] N/A
		Is the proper amount of landscaping in place?	[] Yes []	No[]N/A
		General Inspection		
*	Exi	ts		
		Two means of egress from building.	[] Yes []	No []NR
		Two exits from each floor.	[] Yes []	No []NR
		Exits clear from trash and debris.	[] Yes []	No []NR
		Illuminated exit signs.	[] Yes []	No []NR
	>	Adequate emergency lighting.	[] Yes []	No []NR
*	Do	ors		
	\triangleright	Swing in direction of travel.	[] Yes []	No []NR
		Panic hardware.	[] Yes []	No []NR
		Egress doors 32 inches wide.	[] Yes []	No []NR

Sei	rvice Equipment (Electrical)	
	•	es [] No [] NR
	·	es [] No [] NR
	•	es [] No [] NR es [] No [] NR
	Appliance/Equipment cords in good condition.	5 [] NO [] NN
*	Service Equipment (Plumbing)	
	Restrooms illuminated properly [] Ye	es [] No [] NR
	Restrooms vented properly. [] Ye	s [] No [] NR
	Water heaters installed properly. [] Ye	s [] No [] NR
	> Toilets and sinks drain properly. [] Ye	es [] No [] NR
*	Exterior	
	Free from trash and tall grass. [] Ye	s [] No [] NR
	Adequate parking. [] Ye	es [] No [] NR
	Building area free from hazards. [] Ye	es [] No [] NR
	ADA CHECKLIST	
*	Doors and Entrances	
	> Has at least one handicap accessible entrance.	[] Yes [] No
	Doors has minimum clear opening of 32" wide.	[] Yes [] No
	Doors require minimum effort to open and close slowly.	[] Yes [] No
	➤ Level platform approximately 5'x5' inside and outside of door.	[] Yes [] No
	Door thresholds should be flush or beveled.	[] Yes [] No
.	Rest Rooms	
	Door should swing out with 32" clear opening.	[] Yes [] No
	➤ Room should be approximately 5'x5' with a clear space or	[] Yes [] No
	30"x48" in front to sink, toilet stall, etc	
	Two handrails mounted securely behind or adjacent to toilet.	[] Yes [] No
	➤ Mirror, towel dispenser & shelves not mounted over 40" max height.	[] Yes [] No
	Sink should have 29" clear space underneath (no cabinet).	[] Yes [] No
	Faucets to be lever-operated or push type.	[] Yes [] No
	➤ Toilet stalls at least 4'8"x 3' with door which swings out.	[] Yes [] No
	Urinals to be floor mounted or a max height of 19" from floor.	[] Yes [] No
*	Telephones and Drinking Fountains	
	If offered, at least one public phone must be accessible to the handicap.	[] Yes [] No
	If offered, at least one fountain must be accessible to the handicap.	[] Yes [] No

Saf	ety	and Hazards	
	\triangleright	If an alarm system is available, must include auditory & visual signal.	[] Yes [] No
		Floors should be level and non-slip.	[]Yes [] No
		Exits should be clearly marked.	[] Yes [] No
		Warnings posted clearly near hazards or dangerous areas.	[]Yes [] No
		Tactile floor warnings near the top of stairs.	[] Yes [] No
		Fire alarms should be marked and accessible.	[] Yes [] No
		Corridors should be free of protruding objects.	[] Yes [] No
*	Ra	mps	
	\triangleright	Must be 36" wide (clear space), cannot have a slope steeper than	[] Yes [] No
		1' rise over a distance of 12', and run over 30' without a rest platform.	
		Ramps should have handrails on both sides which extend 1' before and beyond the slope of the ramp.	[]Yes [] No
	\triangleright	Ramps should have a non-slip uninterrupted surface.	[] Yes [] No
		Ramp platforms should be at least 5'x5' with a 6' long flat surface.	[]Yes [] No
*	Wa	alkways	
*		alkways Walkways should be a continuous uninterrupted nonslip surface.	[]Yes [] No
	>	•	[]Yes [] No
	> Sta	Walkways should be a continuous uninterrupted nonslip surface.	[] Yes [] No [] Yes [] No
	> Sta	Walkways should be a continuous uninterrupted nonslip surface.	
	Sta	Walkways should be a continuous uninterrupted nonslip surface. airs and Elevators Stair steps should be at least 11" deep and not exceed 7" in rise.	[] Yes [] No
	Sta	Walkways should be a continuous uninterrupted nonslip surface. Airs and Elevators Stair steps should be at least 11" deep and not exceed 7" in rise. Stair nosing's (under front edge) should be flush, angled, or rounded. Handrails must be on both sides of the stairs and exceeds 12" past	[] Yes [] No [] Yes [] No
*	Sta	Walkways should be a continuous uninterrupted nonslip surface. Airs and Elevators Stair steps should be at least 11" deep and not exceed 7" in rise. Stair nosing's (under front edge) should be flush, angled, or rounded. Handrails must be on both sides of the stairs and exceeds 12" past the bottom and top steps. Elevator cab should have approximately 5'x5' with controls at an appropriate height which can be easily operated.	[] Yes [] No [] Yes [] No [] Yes [] No
*	Sta	Walkways should be a continuous uninterrupted nonslip surface. Airs and Elevators Stair steps should be at least 11" deep and not exceed 7" in rise. Stair nosing's (under front edge) should be flush, angled, or rounded. Handrails must be on both sides of the stairs and exceeds 12" past the bottom and top steps. Elevator cab should have approximately 5'x5' with controls at an	[] Yes [] No [] Yes [] No [] Yes [] No
*	Sta	Walkways should be a continuous uninterrupted nonslip surface. Airs and Elevators Stair steps should be at least 11" deep and not exceed 7" in rise. Stair nosing's (under front edge) should be flush, angled, or rounded. Handrails must be on both sides of the stairs and exceeds 12" past the bottom and top steps. Elevator cab should have approximately 5'x5' with controls at an appropriate height which can be easily operated.	[] Yes [] No [] Yes [] No [] Yes [] No
*	Sta	Walkways should be a continuous uninterrupted nonslip surface. Airs and Elevators Stair steps should be at least 11" deep and not exceed 7" in rise. Stair nosing's (under front edge) should be flush, angled, or rounded. Handrails must be on both sides of the stairs and exceeds 12" past the bottom and top steps. Elevator cab should have approximately 5'x5' with controls at an appropriate height which can be easily operated. rking If the building has a parking lot, at least on space should be designated	[] Yes [] No [] Yes [] No [] Yes [] No