Lawson

HSP Gloss Black

Material Safety Data Sheet

Revision Date

13-Apr-2012

1. CHEMICAL PRODUCT AND COMPANY INFORMATION

Product code

Product name Recommended Use 98761

HSP Gloss Black

Coating

Supplier

Lawson Products, Inc. 1666 East Touhy Avenue Des Plaines, IL 60018 (847)-827-9666

Emergency telephone number

(888) 426-4851

2. HAZARDS IDENTIFICATION

Emergency Overview

Extremely flammable. Contents under pressure. Irritant. Harmful by inhalation.

Aggravated Medical Conditions

None Known.

Principal Routes of Exposure

Eyes. Inhalation.

Potential health effects

Eyes

Exposure to vapors will cause the following effects.

Irritation. Swelling.

Skin

Exposure to vapors will cause the following effects.

Skin Irritation.

Inhalation

Exposure to vapors will cause the following effects. Irritation of the nose or throat. Central nervous system effects. Dizziness. Drowsiness. Headaches. Fatigue. Nausea. Extreme overexposure may cause. Kidney damage. Lung damage. Liver damage. Cardiac abnormalities. Damage to blood. Misuse by deliberately concentrating vapors and inhaling

contents can be harmful or fatal.

Ingestion

May be harmful if swallowed.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	CAS-No	Weight %
Acetone	67-64-1	10-30
N-Butane	106-97-8	7-13
Barium Sulfate	7727-43-7	5-10
Ethylene glycol monopropyl ether	2807-30-9	5-10
Methylisobutyl ketone	108-10-1	3-7
Methyl Propyl Ketone	107-87-9	1-5
Xylene (mix)	1330-20-7	1-5
PM Acetate	108-65-6	1-5
Isobutyl acetate	110-19-0	1-5

4. FIRST AID MEASURES

Eye contact

Remove to fresh air. Rinse thoroughly with plenty of water, also under the eyelids. Seek medical attention

if irritation persists.

Skin contact

Wash area thoroughly with soap and water. Remove

and wash contaminated clothing before re-use.

Ingestion

Call a physician or Poison Control Center

immediately.

Inhalation

Move to fresh air. If symptoms persist, call a

physician.

5. FIRE FIGHTING MEASURES

Flash point °C

Flash point °F

-19 -2

Method

No information available

Product is not self-igniting

Autoignition temperature °C

Autoignition temperature °F

Flammability Limits (% in Air)

Upper

10.9 1.7

Lower

Suitable extinguishing media

Carbon dioxide (CO2). Water spray. Alcohol-resistant foam . Sand.

Special protective equipment for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear

Fire and Explosion Hazards

Aerosol containers may vent, rupture or burst when heated to temperatures above 120°F. Vapors may form explosive mixture in air between upper and lower explosive limits which can be ignited by many sources, such as pilot lights, open flames, electrical motors and switches.

Sensitivity to shock

No information available

Sensitivity to static discharge

No information available.

6. ACCIDENTAL RELEASE MEASURES

Methods for cleaning up

Personnel should wear appropriate protective equipment. Follow all precautions for handling. Please refer to appropriate sections of MSDS for additional information. Evacuate area of unprotected and unnecessary personnel. Do not allow product to reach sewage system, soil, surface or ground water, or any water course. Notify proper authorities if entry occurs. Do not flush with water or aqueous cleansing agents. Use diluted caustic solution. Soak up with inert absorbent material. Dispose of absorbent in accordance with local, state and federal regulations.

7. HANDLING AND STORAGE

Handling

Do not spray on a naked flame or any other incandescent material. Do not smoke. Protect against electrostatic charges.

Storage

Small pressurized containers of flammable product may be stored in areas suitable for ordinary combustibles with respect to construction, drainage, control of ignition sources, and ventilation except that they should not be stored in basements. Keep away from heat. Keep away from direct sunlight. Do not freeze.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Chemical Name	OSHA PEL (TWA)	OSHA PEL (Ceiling)	ACGIH OEL (TWA)	ACGIH OEL (STEL)
Acetone	1000 ppm 2400 mg/m ³		500 ppm	750 ppm
N-Butane	•	-	1000 ppm	-
Barium Sulfate	15 mg/m ³	2	10 mg/m ³	-
Ethylene glycol monopropyl ether	-	-	-	-
Methylisobutyl ketone	100 ppm 410 mg/m ³	-	20 ppm	75 ppm
Methyl Propyl Ketone	200 ppm 700 mg/m ³	-	-	150 ppm
Xylene (mix)	100 ppm 435 mg/m ³	-	100 ppm	150 ppm
PM Acetate	-	<u> </u>	_	7. 4
Isobutyl acetate	150 ppm 700 mg/m³		150 ppm	

Ventilation and Environmental Controls

Adequate ventilation should be provided to keep exposure levels below current acceptable exposure limits.

Hygiene measures

Keep away from food, drink and animal feeding stuffs. Wash hands before breaks and immediately after handling the product.

Respiratory protection

None required if adequate ventilation is provided. Follow OSHA respirator regulations (29 CFR 1910.134) and if necessary, wear a MSHA/NIOSH approved respirator. Wear a NIOSH approved organic vapor/particulate respirator.

Hand Protection

Chemical resistant gloves. Nitrile rubber.

Eye protection

Tightly fitting safety goggles.

Skin and body protection

None necessary under normal conditions

9. PHYSICAL AND CHEMICAL PROPERTIES

 Form
 Aerosol

 Color
 Black

 Odor
 Solvent

Odor Threshold No information available No data available pH Specific Gravity 0.77-0.85 40 PSI @ 70 F Vapor pressure Density No data available No data available Vapor density **Evaporation Rate** No data available Water solubility No data available

VOC Content 46.2%; 462.2 g/l; 3.86 lb/gl

Solids content 31.1%

Partition Coefficient No data available

(n-octanol/water)
Boiling point/range °C -44
Boiling point/range °F -47

Melting point/range °C No data available Melting point/range °F No data available

Flash point °C -19
Flash point °F -2
Ignition temperature °C 230
Ignition temperature °F 446

10. STABILITY AND REACTIVITY

Stability

Stable under normal conditions.

Conditions to avoid

Do not store in temperatures above 120 degrees F.

Incompatability

None known.

Hazardous Decomposition Products

None known.

Polymerization

Hazardous polymerization does not occur

11. TOXICOLOGICAL INFORMATION

Component Information

Chemical Name	LD50 (oral,rat)	LD50 (dermal ,rat/rab bit)	LC50 (inhalation,rat)
Acetone 67-64-1	5800 mg/kg	-	-
N-Butane 106-97-8	-	-	658 mg/L
Barium Sulfate 7727-43-7	-	-	(*)
Ethylene glycol monopropyl ether 2807-30-9	3089 mg/kg	960 μL/kg	-
Methylisobutyl ketone 108-10-1	2080 mg/kg	16000 mg/kg	8.2 mg/L

Product name HSP Gloss Black

Chemical Name	\$3900 E E E E E E E E E E E E E E E E E E	LD50 (dermal ,rat/rab bit)	LC50 (inhalation,rat)
Methyl Propyl Ketone 107-87-9	1600 mg/kg	6500 mg/kg	<u>:-</u>
Xylene (mix)	4300	1700	47635 mg/L
1330-20-7	mg/kg	mg/kg	5000 ppm
PM Acetate	8532	5000	2
108-65-6	mg/kg	mg/kg	
Isobutyl acetate	13400	5000	-
110-19-0	mg/kg	mg/kg	

Synergistic Products

None known

Potential health effects

Sensitization

None known

Chronic toxicity

None known

Mutagenic effects

None known

Teratogenic effects

None known

Reproductive toxicity

None known

Target Organ Effects

Reports have associated prolonged overexposure to solvents with permanent brain and nervous system damage. Prolonged or repeated occupational overexposure may affect the following:. Kidney. Lungs. Liver.

Heart. Blood.

Carcinogenic effects

See table below

Chemical Name	ACGIH OEL - Carcinoge ns	IARC	NTP - Known Carcinoge ns	NTP - Suspected Human Carcinoge ns	OSHA RTK Carcinoge ns
Acetone	A4	Not Listed	Not Listed	Not Listed	Not Listed
N-Butane	Not Listed	Not Listed	Not Listed	Not Listed	Not Listed
Barium Sulfate	Not Listed	Not Listed	Not Listed	Not Listed	Not Listed
Ethylene glycol monopropyl ether	Not Listed	Not Listed	Not Listed	Not Listed	Not Listed
Methylisobutyl ketone	A3	Group 2B	Not Listed	Not Listed	Listed
Methyl Propyl Ketone	Not Listed	Not Listed	Not Listed	Not Listed	Not Listed
Xylene (mix)	A4	Not Listed	Not Listed	Not Listed	Not Listed
PM Acetate	Not Listed	Not Listed	Not Listed	Not Listed	Not Listed
Isobutyl acetate	Not Listed	Not Listed	Not Listed	Not Listed	Not Listed

12. ECOLOGICAL INFORMATION

Acetone

Microtox Data

Photobacterium phosphoreum EC50=14500 mg/L (15 min)

Water Flea Data

Daphnia magna EC5010294 - 17704 mg/L (48 h) Daphnia magna EC5012600 - 12700 mg/L (48 h)

Methylisobutyl ketone

Microtox Data

Photobacterium phosphoreum EC50=79.6 mg/L (5 min)

Water Flea Data

Daphnia magna EC50=170 mg/L (48 h)

Xylene (mix)

Microtox Data

Photobacterium phosphoreum EC50=0.0084 mg/L (24 h)

Water Flea Data

Gammarus lacustris LC50=0.6 mg/L (48 h)

water flea EC50=3.82 mg/L (48 h)

PM Acetate

Water Flea Data

Daphnia magna EC50>500 mg/L (48 h)

Isobutyl acetate

Water Flea Data

Daphnia magna EC50=168 mg/L (24 h)

13. DISPOSAL CONSIDERATIONS

Disposal Information

Dispose in accordance with federal, state, and local regulations. Do not puncture or incinerate. Please recycle empty container whenever possible.

14. TRANSPORTATION INFORMATION

DOT

Consumer commodity, ORM-D

TDG

UN1950 AEROSOLS, flammable, 2.1

15. REGULATORY INFORMATION

Chemical Name	US EPA SARA 313 Emission Reporting
Barium Sulfate	Listed
Ethylene glycol monopropyl ether	
Methylisobutyl ketone	Listed
Xylene (mix)	Listed

State Regulations

Chemical Name	New Jersey -	Pennsylvania	California
	RTK	-RTK	Prop. 65
Acetone	Not Listed	Listed	Not Listed

Chemical Name	New Jersey - RTK	Pennsylvania - RTK	California Prop. 65
N-Butane	Not Listed	Listed	Not Listed
Barium Sulfate	Not Listed	Listed	Not Listed
Ethylene glycol monopropyl ether	Not Listed	Not Listed	Not Listed
Methylisobutyl ketone	Listed	Listed	Carcinogen
Methyl Propyl Ketone	Not Listed	Listed	Not Listed
Xylene (mix)	Not Listed	Listed	Not Listed
PM Acetate	Not Listed	Not Listed	Not Listed
Isobutyl acetate	Listed	Listed	Not Listed

International Inventories

Chemical Name	EINECS	DSL	NDSL	TSCA
Acetone	X	X	-	Х
N-Butane	X	Х	-	Х
Barium Sulfate	X	Χ	-	X
Ethylene glycol monopropyl ether	X	Х	-	Х
Methylisobutyl ketone	X	X	-	X
Methyl Propyl Ketone	X	X	-	X
Xylene (mix)	X	X	-	X
PM Acetate	X	Χ	-	X
Isobutyl acetate	X	X	-	X

CPR

This product has been classified in accordance with the hazard criteria of the Controlled Product Regulations and the MSDS contains all of the information required by the Controlled Product Regulations

16. OTHER INFORMATION

NFPA

Health - 1 Flammability - 4

Reactivity - 3

HMIS

Health - 1 Flammability - 4

Physical Hazard - 3

Prepared By

V. Shargorodsky, Regulatory Affairs Engineer

The information accumulated herein is believed to be accurate, but is not warranted to be, whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.