Pioneer

Quik Stripe Arctic White



Material Safety Data Sheet acc. to ISO/DIS 11014

Printing date 01/06/2006

Reviewed on 01/06/2006

1 Identification of substance

Trade name:

QUIK STRIPE ARCTIC WHITE

Product code:

QSW12

MANUFACTURED FOR: PIONEER MANUFACTURING CO 4529 INDUSTRIAL PKWY CLEVELAND, OH 44135 PHONE NUMBER: 800-877-1500

Emergency information: 800-877-1500

FOR CHEMICAL EMERGENCY
Call INFOTRAC
1-800-535-5053
24 Hrs. per day, 7 days per week

2 Composition/Data on components

Chemical Description: This product is a mixture of the substances listed below with nonhazardous additions.

	components: Calcium Carbonate	15.24%
74-98-6	propane	12.6%
	VM&P Naptha .	9.98%
13463-67-7	titanium dioxide	9.68%
142-82-5	heptane	9.66%
106-97-8	n-butane ·	7.4%
64742-47-8	Mineral Spirits	5.09%

Additional information: For the wording of the listed risk phrases refer to section 3.

3 Hazards identification

Hazard description:



Irritant Flammable

Physical dangers:

Warning! Flammable liquid and vapor in a pressurized container. Keep away from heat, sparks, and flame.

Flammable.

Irritating to eves and respiratory system.

Keep out of the reach of children.

Effects of short-term overexposure:

Vapors cause irritation to the eves, nose, throat, skin, and central nervous system. Symptoms may include dizziness, throat irritation, headache, fatigue, swelling of eyes, and nausea.

Effects of chronic overexposure:

May cause permanent brain and nervous system damage. Repeated overexposure can also damage kidneys. lungs. liver, heart, and blood. Intentional misuse by deliberately inhaling the contents may be

harmful or fatal.

NFPA ratings (scale 0 - 4): Health-

Flammability- 3

Reactivity-HMIS-ratings (scale 0 - 4): Health-

Flammability- 3

Physical Hazard-3

4 First aid measures

After inhalation:

Supply fresh air; consult doctor in case of complaints.

After skin contact: After eye contact: Remove contaminated clothing. Wash exposed area with soap and water.

Move to fresh air. Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

Contact physician or poison control center.

After swallowing:

5 Fire fighting measures

Extinguishing agents:

CO2. sand, extinguishing powder, or water spray. Fight larger fires with water spray or alcohol resistant

foam

Protective equipment:

No special measures required.

6 Accidental release measures

Personal safety

precautions:

Wear protective equipment. Keep unprotected persons away.

(Contd. on page 2)

- USA

WARNING: This product contains a chemical known to the State of California to cause cancer.

Material Safety Data Sheet acc. to ISO/DIS 11014

Printing date 01/06/2006

Reviewed on 01/06/2006

(Contd. of page 1)

Trade name:	QUIK	STRIPE	ARCTIC	WHITE
-------------	------	--------	--------	-------

Environmental safety

precautions:

Do not allow product to reach sewage systems or ground water.

Inform appropriate authorities in case of seepage into water course or sewage system.

Measures for cleaning/

collecting:

Do not flush with water or aqueous cleansing agents. Use diluted caustic solution. Soak up spills with inert absorbent material. Refer to section 13 for disposal information.

7 Handling and storage

Fire/explosion protection:

Do not spray on a naked flame or any incandescent material.

Do not smoke. Protect from electrostatic charges.

Storage requirements:

Observe pressurized container storage regulations. Consult with your local authorities.

Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions.

8 Exposure controls and personal protection:

Com	ponents with limit values that require monitoring at the workplace:
1317	-65-3 Calcium Carbonate
PEL	15*; 5** mg/m³
	*Total dust **Respirable fraction
REL	10*; 5** mg/m³
77.37	*Total dust **Respirable fraction
ILV	10 mg/m ³
74.00	(e)
	3-6 propane
PEL	1800 mg/m³, 1000 ppm
TIV	1800 mg/m³, 1000 ppm (4508) mg/m³, (2500) ppm
	32-5 heptane
PEL	2000 mg/m³, 500 ppm
	Short-term value: Ĉ 1800* mg/m³, C 440* ppm Long-term value: 350 mg/m³, 85 ppm
	*15-min
TIV	Short-term value: 2050 mg/m³, 500 ppm
1	Long-term value: 1640 mg/m³, 400 ppm
106-9	7-8 n-butane
REL	1900 mg/m³, 800 ppm
TLV	1900 mg/m³, 800 ppm
	2-47-8 Mineral Spirits
	200 mg/m³
	As total hydrocarbon vapor; Skin; (P)

Protective hygienic

measures:

Keep away from foodstuffs and animal feed. Wash hands after use.

Breathing equipment:

Protection of hands:

A respirator is generally not necessary when using this product outdoors or in large open areas. In cases of inadequate ventilation, a respiratory protective device should be worn to prevent overexposure. Use suitable respiratory protective device in case of insufficient ventilation.

Protective gloves. The glove material has to be impermeable and resistant to the substance. No glove recommendation can be given.

Eye protection:

Tightly sealed goggles

9 Physical and chemical properties:

Form: Color: Odor: Boiling point/Boiling range:	Aerosol According to trade name description in section 1. Solvent -44°C (-47°F)	
Flash point:	-19°C (-2°F)	
Ignition temperature:	210.0°C (410°F)	
Auto igniting:	Product is not self-igniting.	

(Contd. on page 3)

Material Safety Data Sheet acc. to ISO/DIS 11014

Printing date 01/06/2006

Reviewed on 01/06/2006

Trade name:	QUIK	STRIPE	ARCTIC	WHITE
-------------	------	--------	--------	-------

	(Contd. of page
Danger of explosion:	Stable at normal temperatures. Can may burst when exposed to temperatures exceeding 12 degrees fahrenheit. In use, may form flammable/explosive vapour-air mixture.
Lower Explosion Limit:	1.7 Vol %
Upper Explosion Limit:	10.9 Vol %
Vapor Pressure:	40 PSI, 2750 hPa
Density:	Not determined.
Specific Gravity:	Between 0.77 and 0.90 (Water equals 1.00)
VOC content:	586.3 g/l / 4.89 lb/gl
VOC in weight percent (less acetone	
Water:	22.0 %
Solids content:	31.7 %

10 Stability and reactivity:

Conditions to be avoided: Do not allow the can to exceed 120 degrees Fahrenheit. Stable at normal temperatures.

Possibility of Hazardous

Reactions:

No dangerous reactions known.

11 Toxicological information:

Primary effect on the skin: No irritant effect.

Primary effect on the eye: Irritating effect.

Sensitization:

No sensitizing effects known.

12 Ecological information

Other information:

This product does not contain any chloroflourocarbons (CFC's).chlorinated solvents, or heavy metals

(lead, mercury, cadmium, etc.). No specific ecological data is available for this product.

Acquatic toxicity:

Harmful to aquatic organisms. Hazardous for water, do not empty into drains.

13 Disposal considerations

DISPOSAL METHOD: Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.

Recommendation:

Empty cans should be recycled.

14 Transport information:

Hazard class:

2.1

Identification number: Label

N/A 2.1

ADR/RID class:

5F Gases

UN-Number:

1950

IMDG Class:

Packaging group: EMS Number:

П

F-D,S-U

Marine pollutant: ICAO/IATA Class: No 2.1

Propper shipping name:

Aerosols, Flammable

Consumer Commodity ORM-D

15 Regulations

SARA Section 355 (extremely hazardous substances):

None of the ingredients in this product are listed.

SARA Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

TSCA (Toxic Substances

All ingredients are listed. Control Act):

PROPOSITION 65 Chemicals known to cause cancer:

100-41-4 ethyl benzene

Canadian WHMIS:

Class A. B5---Flammable Aerosols

(Contd. on page 4)

Material Safety Data Sheet acc. to ISO/DIS 11014

Printing date 01/06/2006

Reviewed on 01/06/2006

	K STRIPE ARCTIC WHITE	
		(Contd. of page 3
EPA:		
A= Known human o	carcinogen B= Probable human carcinogen	
C= Possible human	carcinogen	
D= Not classifiable	as to human carcinogenicity: Inadequate human and animal evidence of carcinogenicity (or no dat	a is available).
IARC:		
13463-67-7 titaniur	n dioxide	3
ACGIH TLVs:	A1-designates a confirmed human carcinogen.	
	A2-designates a suspected human carcinogen.	
	A3-designates an animal carcinogen. A4-designates "not classifiable as a human carcinogen".	
13463-67-7 titanium	n dioxide	A4
NIOSH:		
13463-67-7 titaniun	n dioxide	
generalizationeri del servito demper i al desen		A No. of Landson Committee
6 Other information	${f n}$	er de de dans et ex
This information is l	based on our present knowledge. However, this shall not constitute a guarantee for any specific p	roduct feature
and shall not establis	sh a legally valid contractual relationship.	
Contact:	Craig Swafford, Regulatory Affairs. Email: cswafford@seymourpaint.com	